

## Product selection and technical data

Dryer Model	Flowrate @ 7 barg (102 psig)		Dimensions mm (ins)				Pipe Size	Weight kg (lb)
	cfm	m <sup>3</sup> /h	A	B	C	D		
MX102c	240	408	696 (27.4)	326 (12.8)	550 (21.65)	1647 (64.8)	2"	235 (518)
MX103c	360	612	865 (34.1)	495 (19.5)	550 (21.65)	1647 (64.8)	2"	316 (696)
MX103	450	765	865 (34.1)	495 (19.5)	550 (21.65)	1892 (74.5)	2"	355 (782)
MX104	600	1020	1034 (40.7)	664 (26.1)	550 (21.65)	1892 (74.5)	2"	450 (992)
MX105	750	1275	1203 (47.4)	833 (32.8)	550 (21.65)	1892 (74.5)	2 1/2"	543 (1197)
MX106	900	1530	1372 (54.0)	1002 (39.45)	550 (21.65)	1892 (74.5)	2 1/2"	637 (1404)
MX107	1050	1785	1541 (60.7)	1171 (46.1)	550 (21.65)	1892 (74.5)	2 1/2"	731 (1611)
MX108	1200	2040	1710 (67.3)	1340 (52.8)	550 (21.65)	1892 (74.5)	2 1/2"	825 (1818)
MPX110	1380	2346	2223 (87.5)	1470 (57.9)	550 (21.7)	1788 (70.4)	4"	895 (1969)
MPX112	1656	2815	2551 (100.4)	1798 (70.8)	550 (21.7)	1788 (70.4)	4"	1025 (2255)

<b>Maximum operating pressure</b>	13 barg (190 psi g)
<b>Minimum operating pressure</b>	4 barg (58 psi g)
<b>Maximum inlet temperature</b>	50°C (122°F)
<b>Minimum inlet temperature</b>	2°C (35°F)
<b>Noise level</b>	<75 dB(A)
<b>MX (voltage)</b>	85 - 265V ac 50/60Hz
<b>MPX (voltage)</b>	230V ac 50/60Hz 110V ac 50/60Hz



A wide range of donnick hunter preventative maintenance programs are available.

Comprehensive worldwide service packages that can be tailored to match your exact requirements.

